



## PATT A-Ir recessed fitting


LED, 3000K, round, matt white, 38°, incl. driver

The innovative PATT A I recessed fitting is suitable for ceiling thicknesses of up to 25 mm. Rated IP65 it can be used outdoors or in damp areas. This set is available in matt black, matt white, or brushed aluminium as well as in round or square form. Equipped with a powerful, warm white premium COB LED in a rigid mount, as well as the dimmable LED driver included in the scope of supply, the set can be used in any lighting situation. The electrical connection is made directly to the 230V mains supply.

## TECHNICAL DATA

Item no.	114421
IP Code	IP 20 / IP 65
Assembly	Recessed
Assembly details	Ceiling
Dimmable	Yes
Dimming technology	Leading edge, trailing edge
Primary nominal voltage	220-240V ~50/60Hz
Secondary power / voltage	500 mA
Safety class	II
Wattage	11 W
Level of inrush current	2 A
Duration of inrush current	40 µs
Stroboscopic effect (SVM)	0.02
Lumen	910 lm
Colour temperature	3000 Kelvin
Beam angle	38 °
Color	white
CRI	80
LXXBXX data	L70B50
Service life	40000 h
Height	4.5 cm
Diameter	8 cm

## Light Source

916451		<b>Net weight</b>	0.251 kg
		<b>Gross weight</b>	0.299 kg
		<b>Shape of cut-out</b>	round
		<b>Installation depth</b>	6 cm
		<b>Installation diameter</b>	6 cm
		<b>BIG WHITE Page</b>	245