


PATTa-F

recessed fitting, LED, 3000K, square, matt black, 38°, incl. driver


The innovative PATTa F recessed fitting is suitable for ceiling thicknesses of up to 20 mm. Rated IP65 it can be used outdoors or in damp areas. This set is available in matt black, white, or brushed aluminium as well as in round or square form. Equipped with a powerful, warm white premium COB LED in a tiltable mount, as well as dimmable LED driver included in the scope of supply, the set can be used in any lighting situation. The electrical connection is made directly to the 230V mains supply.



TECHNICAL DATA

| | |
|----------------------------|-----------------------------|
| Item no. | 114450 |
| IP Code | IP 20 / IP 65 |
| Impact resistance class | IK 02 |
| Assembly | Recessed |
| Assembly details | Ceiling |
| Dimmable | Yes |
| Dimming technology | Leading edge, trailing edge |
| Primary nominal voltage | 220-240V ~50/60Hz |
| Secondary power / voltage | 500 mA |
| Safety class | II |
| Wattage | 11 W |
| Level of inrush current | 2 A |
| Duration of inrush current | 40 µs |
| Stroboscopic effect (SVM) | 0.02 |
| Lumen | 745 lm |
| Colour temperature | 3000 Kelvin |
| Beam angle | 38 ° |
| Color | black |
| CRI | 80 |
| LXXBXX data | L70B50 |
| Service life | 40000 h |
| Length | 8.3 cm |

Light Source

| | | |
|--------|---|------------------------------|
| 916451 |  | |
| | | Width |
| | | 8.3 cm |
| | | Height |
| | | 6.2 cm |
| | | Net weight |
| | | 0.394 kg |
| | | Gross weight |
| | | 0.397 kg |
| | | Shape of cut-out |
| | | round |
| | | Installation depth |
| | | 6 cm |
| | | Installation diameter |
| | | 7 cm |
| | | BIG WHITE Page |
| | | 247 |