




## H-LIGHT 3

recessed fitting, LED, 2700K, reflector, white, 20°, 11,5W, incl. driver, clip spring

The H-LIGHT 3 recessed fitting series impresses with its simple and elegant design, the integrated warm-white LED module with its narrow 20° beam angle ensures a discreet and ambience-oriented radiance. Thanks to the LED driver included in the set, the luminaire is immediately ready for connection to a 230V power supply.



## TECHNICAL DATA

Item no.	114501
Rotating or tilting	tiltable
IP Code	IP 20
Assembly	Recessed
Assembly details	Ceiling
Dimmable	Yes
Dimming technology	Leading edge, trailing edge
Primary nominal voltage	220-240V ~50/60Hz
Secondary power / voltage	500 mA
Safety class	II
Wattage	11 W
Level of inrush current	2 A
Duration of inrush current	40 µs
Stroboscopic effect (SVM)	0.02
Lumen	540 lm
Colour temperature	2700 Kelvin
Beam angle	20 °
Color	white
CRI	80
LXXBXX data	L70B50
Service life	40000 h
Height	8 cm

## Light Source

916341	
--------	---

<b>Diameter</b>	9 cm
<b>Net weight</b>	0.333 kg
<b>Gross weight</b>	0.394 kg
<b>Shape of cut-out</b>	round
<b>Installation depth</b>	8 cm
<b>Installation diameter</b>	8 cm