




KADUX 3 SET recessed fitting

triple-headed LED, 3000K, rectangular, matt black, 38°, 22W, incl. driver

The KADUX recessed fitting series has a robust housing with appealing, high-quality looks. This LED set is multi-directional, allowing individual focus of the light beam. The KADUX 3 SET comes ready for direct connection to 230V mains and is available in matt black, matt white or brushed aluminium, as well as in single, double, or triple-headed variations.



TECHNICAL DATA

Item no.	115720
Rotating or tilting	cardanic
IP Code	IP 20
Assembly	Recessed
Assembly details	Ceiling
Dimmable	Yes
Dimming technology	Leading edge, trailing edge
Primary nominal voltage	220-240V ~50/60Hz
Secondary power / voltage	350 mA
Safety class	II
Wattage	20 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	35 °C
Level of inrush current	4 A
Duration of inrush current	110 µs
Stroboscopic effect (SVM)	0.01
Lumen	1920 lm
Colour temperature	3000 Kelvin
Beam angle	38 °
Color	black
CRI	80
LXXBXX data	L70B50

Light Source

916451	
--------	---

Service life	40000 h
Length	21 cm
Width	9 cm
Height	8.5 cm
Net weight	0.78 kg
Gross weight	0.863 kg
Shape of cut-out	square
Installation length	20 cm
Installation width	8 cm
Installation depth	8 cm