




## KADUX 2 SET

recessed fitting, double-headed LED, 3000K xl, rectangular, matt white, 30°, 54W, incl. driver, clip springs

The KADUX recessed fitting series has a robust housing with appealing, high-quality looks. This XL Type LED Set is multi-directional, allowing individual focus of the light beam. Its high output, warm white Premium COB LED produces exceptionally powerful illumination. The KADUX 2 SET recessed fitting comes ready for direct connection to 230V mains.



## TECHNICAL DATA

Item no.	115741
Rotating or tilting	cardanic
IP Code	IP 20
Assembly	Recessed
Assembly details	Ceiling
Primary nominal voltage	220-240V ~50/60Hz
Secondary power / voltage	1400 mA
Safety class	II
Wattage	54 W
Minimum ambient temperature	-25 °C
Maximum ambient temperature	35 °C
Network rated standby power	0.41 W
Level of inrush current	15 A
Duration of inrush current	100 µs
Stroboscopic effect (SVM)	0
Lumen	5200 lm
Colour temperature	3000 Kelvin
Beam angle	30 °
Color	white
CRI	80
LXXBXX data	L70B50
Service life	30000 h

## Light Source

916475	
--------	---

Length	37 cm
Width	19.5 cm
Height	12.5 cm
Net weight	2.72 kg
Gross weight	3.271 kg
Shape of cut-out	square
Installation length	34.5 cm
Installation width	17 cm
Installation depth	12.5 cm