




## SUPROS 78

recessed fitting, LED, 3000K, round, tiltable, black, 60° lens, 9W

The SUPROS light series impresses with its multitude of possible applications, excellent LED technology and its harmonious design. With its very high luminous flux, the SUPROS product family is ideally suited to replace power-hungry, conventional lighting installations. The wide-area reflector included in the delivers can be replaced by reflectors with narrower beam angles which are optionally available. This can be done without the need for tools. With the factory-installed LED driver, all the luminaires in the series are suitable for direct connection to the 230V mains supply.



## TECHNICAL DATA

Item no.	116320
Number of different light outlets	1
Rotating or tilting	rotary Bar and tiltable
IP Code	IP 20
Assembly	Recessed
Assembly details	Ceiling
Dimmable	Yes
Dimming technology	trailing edge
Primary nominal voltage	220-240V ~50/60Hz
Secondary power / voltage	250 mA
Safety class	II
Wattage	12 W
Level of inrush current	1 A
Duration of inrush current	68 µs
Stroboscopic effect (SVM)	0.07
Lumen	700 lm
Colour temperature	3000 Kelvin
Beam angle	60 °
Color	black
CRI	80
LXXBXX data	L70B50
Service life	25000 h

## Light Source

916364	
--------	---

<b>Light distribution</b>	rotational symmetric
<b>Light outlet</b>	direct
<b>Height</b>	10.5 cm
<b>Diameter</b>	14 cm
<b>Net weight</b>	0.697 kg
<b>Gross weight</b>	0.813 kg
<b>Shape of cut-out</b>	round
<b>Installation depth</b>	13.1 cm
<b>Installation diameter</b>	13.2 cm