




SUPROS 78

ceiling light, LED, 3000K, round, black, 60° lens


The SUPROS luminaire impresses with its multitude of possible applications, excellent LED technology and its harmonious design. With its very high luminous flux, the SUPROS product family is ideally suited to replace power-hungry, conventional lighting installations. The wide-area reflector included in the delivers can be replaced by reflectors with narrower beam angles which are optionally available. This can be done without the need for tools. With the factory-installed LED driver, all the luminaires in the series are suitable for direct connection to the 230V mains supply.



TECHNICAL DATA

| | |
|-----------------------------------|-------------------|
| Item no. | 116330 |
| Number of different light outlets | 1 |
| Rotating or tilting | tiltable |
| IP Code | IP 20 |
| Assembly | Surface |
| Assembly details | Ceiling |
| Dimmable | Yes |
| Dimming technology | trailing edge |
| Primary nominal voltage | 220-240V ~50/60Hz |
| Secondary power / voltage | 250 mA |
| Safety class | I |
| Wattage | 12 W |
| Level of inrush current | 30 A |
| Duration of inrush current | 40 µs |
| Stroboscopic effect (SVM) | 0.09 |
| Lumen | 700 lm |
| Colour temperature | 3000 Kelvin |
| Beam angle | 60 ° |
| Color | black |
| CRI | 80 |
| LXXBXX data | L70B50 |
| Service life | 25000 h |

Light Source

| | | | |
|--------|---|---------------------------|----------------------|
| 916364 |  | Light distribution | rotational symmetric |
| | | Light outlet | direct |
| | | Height | 15.8 cm |
| | | Diameter | 7.8 cm |
| | | Net weight | 0.605 kg |
| | | Gross weight | 0.664 kg |