




## LIPSY 36 M KELVIN CONTROL

wall and ceiling light, LED, 2700-6500K, white, Master

The KELVIN CONTROL MASTER variant of the popular LIPSY 36 M KELVIN CONTROL ceiling light comes in two sizes and allows colour light control using a remote control and can also be extended using the corresponding KELVIN CONTROL SLAVE version. It is also possible to be combined with all the items in our KELVIN CONTROL range. The luminaire features a cover made of acrylic glass which is fastened to a steel mounting bracket. Thanks to its built-in power supply, the LIPSY ceiling light comes ready for direct connection to the 230V mains supply.



### TECHNICAL DATA

Item no.	134050
IP Code	IP 20
Assembly	Surface
Assembly details	Ceiling,Wall
Dimmable	Yes
Dimming technology	Dim-to-Warm
Primary nominal voltage	100-240V ~50/60Hz
Secondary power / voltage	24 V
Safety class	I
Wattage	39 W
Level of inrush current	36 A
Duration of inrush current	125 µs
Lumen	2300-2900 lm
Colour temperature	2700-6500 Kelvin
Beam angle	120 °
Color	white
CRI	90
LXXBXX data	L70B50
Service life	25000 h
Light distribution	rotational symmetric
Light outlet	direct
Height	11 cm

<b>Diameter</b>	35 cm
<b>Net weight</b>	0.971 kg
<b>Gross weight</b>	1.352 kg