




## LIPSY 50 S KELVIN CONTROL

wall and ceiling light, LED, 2700-6500K, white, Slave

The KELVIN CONTROL SLAVE variant of the popular LIPSY 50 S KELVIN CONTROL ceiling light comes in two sizes and allows an expansion of the colour light control of a KELVIN CONTROL MASTER variant. It can also be combined with all the items in our KELVIN CONTROL range. The luminaire features a cover made of acrylic glass which is fastened to a steel mounting bracket. Thanks to its built-in power supply, the LIPSY ceiling light comes ready for direct connection to the 230V mains supply.



### TECHNICAL DATA

Item no.	134061
IP Code	IP 20
Assembly	Surface
Assembly details	Ceiling,Wall
Dimmable	Yes
Dimming technology	Dim-to-Warm
Primary nominal voltage	220-240V ~50/60Hz
Secondary power / voltage	24 V
Safety class	I
Wattage	52 W
Level of inrush current	27 A
Duration of inrush current	150 µs
Lumen	3600-4500 lm
Colour temperature	2700-6500 Kelvin
Beam angle	120 °
Color	white
CRI	80
LXXBXX data	L70B50
Service life	25000 h
Light distribution	rotational symmetric
Light outlet	direct
Height	13.5 cm

<b>Diameter</b>	48.5 cm
<b>Net weight</b>	1.57 kg
<b>Gross weight</b>	2.194 kg