




KALU

wall and ceiling light, triple-headed, QPAR111, round, brushed aluminium, max. 225 W

The puristic design of KALU ceiling light is a guarantor for absolutely individual alignment of lamp heads, optionally equipped with halogen or suitable LED ES111 lamps. The light can also be dimmed which offers even more installation possibilities. Available in several colour versions KALU ceiling light is supplied ready for direct connection to 230V mains supply.



Tekniske data

Item no.	147326
Sokkel	GU10
Lyskilde	QPAR111
Antal fatninger	3
Lyskilde inkluderet	Nej
Rotation	90 °
Rotation	350 °
IP klasse	IP20
Montering	Surface
Monterings detaljer	Ceiling, Wall
Primær spænding	220-240V ~50/60Hz
IP Tæthedsgard	I
Watt	75 W
Max omgivelsestemperatur	40 °C
Farve	aluminum
Længde	45 cm
Bredde	9 cm
Højde	18 cm
Nettovægt	1.288 kg
Bruttovægt	1.693 kg
BIG WHITE side	405

Anbefalet lyskilde

1005274	QPAR111 GU10 , trans- parent LED light, 8W 2700K CRI90 38°
1005298	LED lamp , QPAR111 GU10 12W 680lm 3000K CRI90 55° Dimmable
1005297	LED lamp , QPAR111 GU10 12W 670lm 2700K CRI90 55° Dimmable
1005299	LED lamp , QPAR111 GU10 12W 750lm 4000K CRI90 55° Dimmable