




## DOWNUNDER PUR 155

recessed fitting, LED, 3000K, square, white, L/W/H 12/3.2/15.5 cm, incl. leaf springs

Aluminium recessed wall light of our DOWNUNDER LED series. The not visibly mounted LED emits the light indirectly onto the surface to be illuminated. This guarantees glare-free illumination of walkways and much more. The DOWNUNDER PUR 120 recessed fitting is available in white colour version. To operate the recessed fitting, a suitable LED driver is required providing 480mA. A mounting frame for installation in masonry can be ordered from the accessory. This luminaire contains built-in LED lamps.



## TECHNICAL DATA

Item no.	151952
IP Code	IP 20
Assembly	Recessed
Assembly details	Wall
Secondary power / voltage	500 mA
Safety class	III
Wattage	5.2 W
Lumen	230 lm
Colour temperature	3000 Kelvin
Color	white
CRI	80
LXXBXX data	L70B50
Service life	30000 h
Light distribution	symmetric
Light outlet	direct
Risk Group	2
Width	12 cm
Height	15.5 cm
Depth	3.2 cm
Net weight	0.242 kg
Gross weight	0.317 kg
Shape of cut-out	square

## Light Source

916412	
--------	---

## Accessories

151962	FLUSH-MOUNTED FRAME , for DOWNUNDER PUR 155, L/H 18/20.5 cm
1007226	LED driver 21W 500mA
1007227	LED driver 20W 350mA- /500mA PHASE
1007229	LED driver 25W 150-700-mA DALI TOUCH

Installation length	14 cm
Installation width	10.5 cm
Installation depth	3.5 cm
BIG WHITE Page	242