




ENOLA_C

ceiling light, LED, 3000K, round, white, 35°

The puristic ceiling mounted light ENOLA_C consists of a cylindrical aluminium construction and is equipped with a high-performance COB LED with warm white light colour. By the incorporated LED driver, the electrical connection is made directly to 230V mains supply. As an accessory for the cylindrical spot, we also offer suitable decorative rings with a textured glass diffuser. This luminaire contains built-in LED lamps.



TECHNICAL DATA

| | |
|----------------------------|-------------------|
| Item no. | 152101 |
| IP Code | IP 20 |
| Assembly | Surface |
| Assembly details | Ceiling |
| Primary nominal voltage | 220-240V ~50/60Hz |
| Secondary power / voltage | 500 mA |
| Safety class | I |
| Wattage | 11 W |
| Level of inrush current | 4.7 A |
| Duration of inrush current | 30 µs |
| Stroboscopic effect (SVM) | 0.01 |
| Lumen | 1020 lm |
| Colour temperature | 3000 Kelvin |
| Beam angle | 35 ° |
| Color | white |
| CRI | 80 |
| LXXBXX data | L70B50 |
| Service life | 40000 h |
| Height | 10.7 cm |
| Diameter | 10 cm |
| Net weight | 0.54 kg |
| Gross weight | 0.65 kg |

Light Source

| | | | |
|--------|---|----------------|-----|
| 916476 |  | BIG WHITE Page | 259 |
|--------|---|----------------|-----|