



## KARDATRACK

pendant for 3-phase 240V track, four-headed, QR-L-P111, silver-grey, max. 200W, incl. 3-phase adapter

Four-headed low-voltage spot KARDATRACK with suitable adapter for the 3-phase 240V track system. By the nature of their mountings, the four bulbs within the frame can be independently tilted and turned in a multi-directional manner. The electronic transformer, which is dimmable, is located in the middle part of the frame. With the G53 socket fitted, the luminaire is suitable for halogen and LED lamps with a diameter of up to 11.1 cm.

## TECHNICAL DATA

|                           |                                       |
|---------------------------|---------------------------------------|
| Item no.                  | 154512                                |
| Socket                    | G53                                   |
| Lamp                      | QR111                                 |
| Number of sockets         | 4                                     |
| Lamps included            | No                                    |
| Rotating or tilting       | rotary Bar and tiltable               |
| IP Code                   | IP 20                                 |
| Assembly                  | Surface                               |
| Assembly details          | Ceiling,Track Ceiling,Track Wall,Wall |
| Primary nominal voltage   | 220-240V ~50/60Hz                     |
| Secondary power / voltage | 12 V                                  |
| Safety class              | I                                     |
| Wattage                   | 50 W                                  |
| Color                     | grey                                  |
| Light outlet              | direct                                |
| Length                    | 86.5 cm                               |
| Width                     | 19 cm                                 |
| Height                    | 18 cm                                 |
| Net weight                | 2.653 kg                              |
| Gross weight              | 3.28 kg                               |

## Recommended lamp

|        |   |
|--------|---|
| 560234 | PHILIPS MASTER LED<br>AR111 , CRI90, 15W, 40°,<br>3000K, dimmable |
| 560231 | PHILIPS MASTER LED<br>AR111 , CRI90, 15W, 24°,<br>2700K, dimmable |
| 560233 | PHILIPS MASTER LED<br>AR111 , CRI90, 15W, 24°,<br>3000K, dimmable |
| 560232 | PHILIPS MASTER LED<br>AR111 , CRI90, 15W, 40°,<br>2700K, dimmable |