


I-VIDUAL

LED panel for grid ceilings, 3000K, silver-grey, L/W 61.7/61.7 cm

The 62 x 62 cm grid I-VIDUAL, available with a number of different colours of light, offers a modern and space saving solution for efficient basic lighting needs. Due to the variable constant current power supply of 1000mA to 1050mA, various standard or dimmable drivers can be used. With this product you reach a pleasant, homogeneous and glare-free lighting feeling. Ideal as a replacement for old tube systems.



TECHNICAL DATA

Item no.	158753
IP Code	IP 20
Assembly	Recessed
Assembly details	Ceiling
Secondary power / voltage	1000/1050 mA
Safety class	III
Lumen	3250 lm
Colour temperature	3000 Kelvin
Beam angle	110 °
Color	grey
CRI	80
LXXBXX data	L70B50
Service life	30000 h
Light outlet	direct
Length	61.7 cm
Width	61.7 cm
Height	1.3 cm
Net weight	4.229 kg
Gross weight	5.056 kg
Shape of cut-out	square
Installation depth	5 cm

Accessories

464176	LED DRIVER , 40W, 1000mA, incl. strain relief, dimmable
464170	LED DRIVER , 40W, 1000mA, incl. strain relief
158791	CEILING PLATE , for LED PANEL, I-VIDUAL and I-VIDUAL LED PANEL, white
158774	INSTALLATION FRAME , for I-VIDUAL LED panel, silver-grey, L/W 62.5/62.5 cm
464804	LED DRIVER , 40W, 1050mA, triac dimmable
158799	SUSPENSION SET , for LED PANEL, I-VIDUAL and I-VIDUAL LED PANEL, steel wire and Y-wire suspension
464032	TCI LED DRIVER , 50VA, 350-1050mA, dip switch, incl. strain relief, DALI dimmable
158772	INSTALLATION FRAME , for LED-PANEL and I-VIDUAL, white matt, L/W/H 62.5/62.5/5.5 cm