


BIMA 1

spot for 240V track EASYTEC II, QPAR51, single-headed, black, max. 50W

BIMA 1 swivelling and tiltable 240V spot with suitable adapter for the EASYTEC II track system. The luminaire is made of aluminium and, thanks to the GU10 socket, is suitable for both halogen and LED lamps.



TECHNICAL DATA

| | |
|---------------------------|---------------------------------------|
| Item no. | 184450 |
| Socket | GU10 |
| Number of sockets | 1 |
| Tilt range | 180 ° |
| Horizontal rotation range | 350 ° |
| Rotating or tilting | rotary Bar and tiltable |
| IP Code | IP 20 |
| Assembly | Surface |
| Assembly details | Ceiling,Track Ceiling,Track Wall,Wall |
| Primary nominal voltage | 220-240V ~50/60Hz |
| Safety class | I |
| Wattage | 50 W |
| Color | black |
| Light outlet | direct |
| Length | 8 cm |
| Height | 15.5 cm |
| Diameter | 6 cm |
| Net weight | 0.336 kg |
| Gross weight | 0.401 kg |

Recommended lamp

| | |
|---------|--|
| 1005077 | LED lightbulb QPAR51 , GU10, 2700K, black |
| 1005273 | QPAR51 GU10 , LED light, 6W 2200 2700K CRI90 36° |
| 1005083 | LED lightbulb QPAR51 , GU10, 4000K, black |
| 1005080 | LED lightbulb QPAR51 , GU10, 3000K, black |