




ADJUST 190

outdoor inground fitting, QR111, IP67, round, stainless steel 304, max. 50W

Walkable, low-voltage recessed ground luminaire with round stainless steel cover and partially frosted glass. Rated IP67, it is suitable for outdoor use. To ensure accurate illumination, the lamp is adjustable. The electrical connection is made directly to 230V mains supply via the incorporated transformer. For simplified mounting, an installation housing is included.



TECHNICAL DATA

Item no.	227090
Socket	G53
Lamp	QR111
Number of sockets	1
Lamps included	No
Tilt range	20 °
Horizontal rotation range	90 °
Rotating or tilting	rotary Bar and tiltable
IP Code	IP 67
Assembly	Recessed
Assembly details	Ground
Mechanical loading	1.5 t
Primary nominal voltage	220-240V ~50/60Hz
Secondary power / voltage	12 V
Safety class	I
Wattage	50 W
Temperature at glass (light emission)	120 °C
Light outlet	direct
Depth	13.5 cm
Diameter	19 cm
Net weight	2.32 kg
Gross weight	2.485 kg

Shape of cut-out	round
Installation depth	14 cm
Installation diameter	18 cm

Recommended lamp

560234	PHILIPS MASTER LED AR111 , CRI90, 15W, 40°, 3000K, dimmable
560231	PHILIPS MASTER LED AR111 , CRI90, 15W, 24°, 2700K, dimmable
560233	PHILIPS MASTER LED AR111 , CRI90, 15W, 24°, 3000K, dimmable
560232	PHILIPS MASTER LED AR111 , CRI90, 15W, 40°, 2700K, dimmable