



## TRAIL-LITE 60

outdoor inground fitting, LED, 3000K, IP65, stainless steel 316, frosted glass insert

The multiple LED fitted floor and wall light TRAIL-LITE 60 can also be used for outdoor applications by its IP65 protection. We alternatively offer other colours of light and frosted or faceted glass covers. For simplified mounting, a mounting pot is included in the delivery. The electrical connection is made through the supply of a separately available conventional 12V low-voltage transformer.

## TECHNICAL DATA

Item no.	227462
IP Code	IP 65
Impact resistance class	IK 08
Assembly	Recessed
Assembly details	Ground,Wall
Primary nominal voltage	12V ~50/60Hz
Safety class	III
Wattage	0.3 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	45 °C
Temperature at glass (light emission)	28 °C
Lumen	4 lm
Colour temperature	3000 Kelvin
Color	stainless steel
CRI	80
LXXBXX data	L70B50
Service life	20000 h
Light outlet	direct
Risk Group	0
Net weight	0.16 kg
Gross weight	0.189 kg
Shape of cut-out	round

<b>Installation depth</b>	7 cm
<b>Installation diameter</b>	4 cm
<b>BIG WHITE Page</b>	848