






NAUTILUS

outdoor spot, QR-C51, IP67, stainless steel 304, max. 35W

The mobile spotlights of the NAUTILUS family are the Plug & Play best-sellers from SLV, which have enhanced a countless number of commercial and private outdoor areas for many years. The reasons are obvious: Uncompromising quality with regard to durability and flexibility. Be it harsh winter nights or warm summer evenings, a NAUTI-LUS outdoor fitting will adorn the garden with unmatched ambience and illuminating effects. Regardless of whether you illuminate your flowers, trees or water features with Nautilus. The NAUTILUS family has a wide range of versions with different models, designs and colours, with a plug or an open cable end, with an installation plate or an earth spike. With versions with a GU10 socket, please note the maximum dimensions and Wattages for the lamp that is going to be used (not included in scope of supply). When are you going to let yourself be impressed with the wide range of advantages of the SLV classic?



TECHNICAL DATA

SocketGX5.3LampQR-C51Number of sockets1Lamps includedNoTilt range180 °Rotating or tiltingtiltableIP CodeIP 67Impact resistance classIK 03AssemblySurfaceAssembly detailsCeiling,Ground,WallPrimary nominal voltage12V ~50HzSafety classIIIWattage35 WColorstainless steelLight outletdirectHeight12.5 cmDiameter10 cmNet weight0.822 kg	Item no.	229090
Number of sockets1Lamps includedNoTilt range180 °Rotating or tiltingtiltableIP CodeIP 67Impact resistance classIK 03AssemblySurfaceAssembly detailsCeiling,Ground,WallPrimary nominal voltage12V ~50HzSafety classIIIWattage35 WColorstainless steelLight outletdirectHeight12.5 cmDiameter10 cm	Socket	GX5.3
Lamps includedNoTilt range180 °Rotating or tiltingtiltableIP CodeIP 67Impact resistance classIK 03AssemblySurfaceAssembly detailsCeiling,Ground,WallPrimary nominal voltage12V ~50HzSafety classIIIWattage35 WColorstainless steelLight outletdirectHeight12.5 cmDiameter10 cm	Lamp	QR-C51
Tilt range180 °Rotating or tiltingtiltableIP CodeIP 67Impact resistance classIK 03AssemblySurfaceAssembly detailsCeiling,Ground,WallPrimary nominal voltage12V ~50HzSafety classIIIWattage35 WColorstainless steelLight outletdirectHeight12.5 cmDiameter10 cm	Number of sockets	1
Rotating or tiltingtiltableIP CodeIP 67Impact resistance classIK 03AssemblySurfaceAssembly detailsCeiling,Ground,WallPrimary nominal voltage12V ~50HzSafety classIIIWattage35 WColorstainless steelLight outletdirectHeight12.5 cmDiameter10 cm	Lamps included	No
IP CodeIP 67Impact resistance classIK 03AssemblySurfaceAssembly detailsCeiling,Ground,WallPrimary nominal voltage12V ~50HzSafety classIIIWattage35 WColorstainless steelLight outletdirectHeight12.5 cmDiameter10 cm	Tilt range	180 °
Impact resistance classIK 03AssemblySurfaceAssembly detailsCeiling,Ground,WallPrimary nominal voltage12V ~50HzSafety classIIIWattage35 WColorstainless steelLight outletdirectHeight12.5 cmDiameter10 cm	Rotating or tilting	tiltable
AssemblySurfaceAssembly detailsCeiling,Ground,WallPrimary nominal voltage12V ~50HzSafety classIIIWattage35 WColorstainless steelLight outletdirectHeight12.5 cmDiameter10 cm	IP Code	IP 67
Assembly detailsCeiling,Ground,WallPrimary nominal voltage12V ~50HzSafety classIIIWattage35 WColorstainless steelLight outletdirectHeight12.5 cmDiameter10 cm	Impact resistance class	IK 03
Primary nominal voltage12V ~50HzSafety classIIIWattage35 WColorstainless steelLight outletdirectHeight12.5 cmDiameter10 cm	Assembly	Surface
Safety classIIIWattage35 WColorstainless steelLight outletdirectHeight12.5 cmDiameter10 cm	Assembly details	Ceiling,Ground,Wall
Wattage 35 W Color stainless steel Light outlet direct Height 12.5 cm Diameter 10 cm	Primary nominal voltage	12V ~50Hz
Color stainless steel Light outlet direct Height 12.5 cm Diameter 10 cm	Safety class	111
Light outlet direct Height 12.5 cm Diameter 10 cm	Wattage	35 W
Height 12.5 cm Diameter 10 cm	Color	stainless steel
Diameter 10 cm	Light outlet	direct
	Height	12.5 cm
Net weight 0.822 kg	Diameter	10 cm
	Net weight	0.822 kg
Gross weight 0.916 kg	Gross weight	0.916 kg
BIG WHITE Page 697	BIG WHITE Page	697



Recommended lamp

1001574	Philips Master LED Spot , MR16, 5W, 2700K, 36°, dimmable
1001575	Philips Master LED MR16 5W , 3000K, 36°