




GALEN LED PROFILE

outdoor façade light, LED, 3000K, IP65, 1 m, silver-grey, 25W

Aluminium panel equipped with 18 powerful LEDs for effective lighting. Thanks to the pre-fitted installation bracket, it can be installed directly on the wall, ceiling and floor. With IP65 protection class, the tiltable panel is also suitable for outdoor use. The electrical connection of the panel available in daylight white and warm-white is done using the built-in connection lead to a 24V DC voltage power supply.



TECHNICAL DATA

Item no.	229482
Rotating or tilting	tiltable
IP Code	IP 65
Assembly	Surface
Assembly details	Ceiling,Ground,Wall
Primary nominal voltage	24V
Safety class	III
Wattage	23 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	45 °C
Lumen	1330 lm
Colour temperature	3000 Kelvin
Beam angle	25 °
Color	grey
CRI	80
LXXBXX data	L70B50
Service life	30000 h
Width	100 cm
Height	3.2 cm
Depth	7 cm
Net weight	1.603 kg
Gross weight	1.897 kg

Light Source

916557	
--------	---

Accessories

470544	LED POWER SUPPLY , 36W, 24V
1005383	LED power supply , 60W 24V