


BENDO

outdoor floor stand, LED, 3000K, IP55, anthracite, L/W/H 47.5/21/225 cm, 12W

The angled aluminium BENDO floor stand is fitted with a large number of powerful LEDs. With protection class IP55, it is suitable for outdoor use. Available in three sizes, it is supplied with open cable ends for simple installation. A concrete anchor, connection box and T-connection box are available as an option. This luminaire contains built-in LED lamps. The LED cannot be changed in the luminaire.



TECHNICAL DATA

Item no.	231845
Number of different light outlets	1
IP Code	IP 55
Impact resistance class	IK 06
Impact resistance	1 Joule
Assembly	Surface
Assembly details	Ground, Ground with Acc.
Dimmable	Yes
Dimming technology	Leading edge
Primary nominal voltage	220-240V ~50/60Hz
Safety class	I
Wattage	31 W
Minimum ambient temperature	-25 °C
Maximum ambient temperature	32 °C
Temperature at glass (light emission)	60 °C
Lumen	1800 lm
Colour temperature	3000 Kelvin
Beam angle	80 °
Color	anthracite
CRI	80
LXXBXX data	L70B50
Service life	35000 h

Light distribution	symmetric
Light outlet	direct
Length	47.5 cm
Width	21 cm
Height	225 cm
Net weight	7.236 kg
Gross weight	10.501 kg

Accessories

228726	T-CONNECTION BOX , black, IP68
228730	CONNECTION BOX , 3-pin, IP68
231849	CONCRETE ANCHOR , for BENDO outdoor floor stand, silver