




DISOS

outdoor floodlight, LED, 4000K, black, 12W

Powerful DISOS LED floodlight to light up areas and courtyards. With a tiltable installation bracket and protection class Ip65, the floodlight is suitable for outdoor installation on the wall or on the floor. The electrical connection of the floodlight, which comes in cold-white, is done using the built-in driver and connection lead directly to the 230V mains supply. Various wall brackets are available for easy wall mounting. This luminaire contains built-in 10.5W LED lamps.



TECHNICAL DATA

Item no.	232350
Number of different light outlets	1
Rotating or tilting	tiltable
IP Code	IP 65
Impact resistance class	IK 06
Impact resistance	1 Joule
Assembly	Surface
Assembly details	Ground,Wall
Primary nominal voltage	220-240V ~50/60Hz
Secondary power / voltage	390 mA
Safety class	I
Wattage	12 W
Lumen	1200 lm
Colour temperature	4000 Kelvin
Beam angle	110°
Color	black
CRI	80
LXXBXX data	L70B50
Service life	35000 h
Light distribution	symmetric
Light outlet	direct
Length	14 cm
	-



Width	6 cm
Height	18 cm
Net weight	0.98 kg
Gross weight	1.095 kg

Accessories

234340	Wall bracket , for Outdoor Beam and MILOX flood- light, black, 50cm
234350	WALL BRACKET , for SPOODI 15/20/31, black, 80 cm
228730	CONNECTION BOX , 3-pin, IP68