




## QUAD 2

wall light, LED, 3000K, IP44, square, up/down, white, 6W


The QUAD 2 wall light is available in several colours, and fitted with a powerful, warm white LEDs. The two oppositely arranged light sources create two similar light beams (UP/DOWN). The electrical connection of the aluminium luminaire is made directly to the 230V mains supply using the built-in driver. Thanks to its IP44 protection class, the luminaire is suitable for outdoor use.



## TECHNICAL DATA

Item no.	232471
Number of different light outlets	2
IP Code	IP 44
Assembly	Surface
Assembly details	Wall
Primary nominal voltage	100-277V ~50/60Hz
Secondary power / voltage	700 mA
Safety class	I
Wattage	6.4 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	50 °C
Level of inrush current	5 A
Duration of inrush current	25 µs
Stroboscopic effect (SVM)	0.02
Lumen	250 lm
Colour temperature	3000 Kelvin
Beam angle	60 °
Color	white
LXXBXX data	L70B50
Service life	30000 h
Width	4 cm
Height	12.4 cm

## Light Source

916521	 The logo for AGG, consisting of the letters 'A' and 'G' stacked vertically in a white box, followed by a red arrow pointing to the right containing the letter 'G'.
<b>Depth</b>	9.5 cm
<b>Net weight</b>	0.647 kg
<b>Gross weight</b>	0.7 kg