




## SPOODI SENSOR

LED Outdoor surface-mounted wall light, 30W, black, 4000K

SPOODI SENSOR powerful LED spotlight, for illuminating areas and spaces. By means of the swivelling mounting bracket and its IP65 protection class, the spotlight is suitable for mounting on exterior walls. The spotlight is connected directly to the 230V mains voltage supply. The spotlight, which is available with two different housings and light colours and also wattages, has a built-in infrared motion sensor. This is easy to adjust using the remote control.



## TECHNICAL DATA

Item no.	232890
Number of different light outlets	1
Rotating or tilting	tiltable
IP Code	IP 65
Impact resistance class	IK 04
Impact resistance	0.5 Joule
Assembly	Surface
Assembly details	Wall
Primary nominal voltage	220-240V ~50/60Hz
Safety class	I
Wattage	30 W
Minimum ambient temperature	-10 °C
Maximum ambient temperature	40 °C
Level of inrush current	70.6 A
Duration of inrush current	170 µs
Lumen	2500 lm
Colour temperature	4000 Kelvin
Beam angle	100 °
Color	black
CRI	80
LXXBXX data	L70B50
Service life	30000 h

## Accessories

234340	Wall bracket , for Outdoor Beam and MILOX flood-light, black, 50cm
234350	WALL BRACKET , for SPOODI 15/20/31, black, 80 cm
234354	WALL MOUNTING BRACKET , for OUTDOOR BEAM and MILOX, silver, 80 cm
234344	WALL MOUNTING BRACKET , for OUTDOOR BEAM and MILOX, silver, 50 cm

Light distribution	axis symmetric
Light outlet	direct
Length	20 cm
Width	4 cm
Height	20.5 cm
Net weight	1.498 kg
Gross weight	1.637 kg