




DASAR PROJECTOR

outdoor floodlight, LED, 3000K, IP68, stainless steel 316, 12-24V, 7W

The accessible high-voltage inground light DASAR Projector LED PRO impresses with its stainless steel screen and glass cover in a partial satin finish. Its IP 68 protection class makes it ideal for outdoor use. The rotatable and pivoting GU10 fitting allows flexible alignment of the light cone. And last but not least, it is the LED lifespan of 25,000 that makes the outdoor ground spike light LED a long-lasting companion. Experience light with SLV – your innovative partner for all kinds of outdoor lights for 40 years.



TECHNICAL DATA

Item no.	233570
Rotating or tilting	tiltable
IP Code	IP 68
Assembly	Surface
Assembly details	Ceiling,Ceiling with Acc.,Ground,Ground with Acc.,Wall,Wall with Acc.
Primary nominal voltage	12-24V
Safety class	III
Wattage	6.5 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	40 °C
Stroboscopic effect (SVM)	0
Lumen	520 lm
Colour temperature	3000 Kelvin
Beam angle	40 °
Color	stainless steel
CRI	80
LXXBXX data	L70B50
Service life	25000 h
Length	7.2 cm
Width	10 cm
Height	10.8 cm
Net weight	1.146 kg

Light Source

954802	
--------	---

Accessories

233582	INSTALLATION PLATE , for DASAR PROJECTOR outdoor floodlight, stain- less steel 316
1005444	LED Power supply , 15W 12V
900011	PLASTIC EARTH SPIKE , black, length 17.5cm
233580	EARTH SPIKE , for DA- SAR PROJECTOR, stainless steel 316
1005445	LED Power supply , 15W 24V

Gross weight	1.229 kg
BIG WHITE Page	698