






## **BIG THEO WALL**

outdoor wall light, double-headed, LED, 3000K, Flood down/Beam up, silver-grey, W/H/D 13/29/13.5 cm

The BIG THEO WALL Flood down/Beam up LED wall light is made of aluminium and glass. Thanks to its two built-in LEDs, the mounted luminaire produces two different cones of light (upper light outlet a narrow cone, lower light outlet a wide cone). It is suitable for use outdoors thanks to its IP44 protection class. Thanks to the built-in LED driver, the electrical connection of the luminaire, which comes in several colour versions, is made directly to the 230V mains supply. In addition, the BIG THEO series includes wall and ceiling lights and is therefore universally deployable. This luminaire includes built-in LED lamps.



## **TECHNICAL DATA**

Item no.	234515
Number of different light outlets	2
IP Code	IP 44
Impact resistance class	IK 02
Impact resistance	0.2 Joule
Assembly	Surface
Assembly details	Wall
Primary nominal voltage	220-240V ~50/60Hz
Secondary power / voltage	500 mA
Safety class	1
Wattage	29 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	45 °C
Level of inrush current	30 A
Duration of inrush current	45 µs
Stroboscopic effect (SVM)	0.03
Lumen	2130 lm
Colour temperature	3000 Kelvin
Beam angle	24 °
Color	anthracite
CRI	80
LXXBXX data	L70B50



## **Light Source**

916394	A E
916416	↑ F

Service life 25000 h   Width 13 cm   Height 29 cm   Depth 13.5 cm   Net weight 2.428 kg		
Height 29 cm   Depth 13.5 cm	Service life	25000 h
Depth 13.5 cm	Width	13 cm
•	Height	29 cm
Net weight 2.428 kg	Depth	13.5 cm
	Net weight	2.428 kg
Gross weight 2.644 kg	Gross weight	2.644 kg
BIG WHITE Page 735	BIG WHITE Page	735