




P-LIGHT 27

wall and ceiling light, emergency exit light, LED, 6000-K, white, L/W/H 26.5/4.5/21 cm, 3,5W

The P-LIGHT 27 emergency lighting system is suitable for use as a wall and ceiling light. The safety lights are fitted with a built-in Ni-MH battery with an automatic self-test. The detection range is 24 m. The emergency operating time of the luminaires is three hours. The luminaires can be operated permanently switched on / stand-by operation. The luminaire is connected directly to the 230V mains supply. Other variants of the P-LIGHT series are available. The luminaire is supplied with three signs with different arrow directions (right / left / down). As an option, other signs are available.



TECHNICAL DATA

Item no.	240000
Number of different light outlets	1
IP Code	IP 20
Assembly	Surface
Assembly details	Ceiling, Wall
Primary nominal voltage	220-240V ~50Hz
Safety class	II
Wattage	3.5 W
Lumen	32 lm
Colour temperature	6000 Kelvin
Color	white
CRI	80
LXXBXX data	L70B50
Service life	25000 h
Width	26.5 cm
Height	21 cm
Depth	4.5 cm
Net weight	0.843 kg
Gross weight	1.06 kg

Accessories

240020	RECHARGEABLE BATTERY , for P-LIGHT, 3.6V, 900mA
240007	PICTOGRAM FOILS , for P-LIGHT emergency exit light, set of 4, diagonal arrow in all directions, L/H 24/13.1 cm