




## P-LIGHT

ceiling light, LED, 6000K, IP65, rectangular, white, 6,5W

P-LIGHT suitable for use as emergency lighting for surface-mounted wall and ceiling lights. The safety lights are fitted with two built-in Ni-MH batteries with an automatic self-test and detection range of 30m. The emergency operating time of the luminaires is three hours. The luminaires can be operated permanently switched on / stand-by operation. The electrical connection is directly to the 230V supply. Other variants of the P-LIGHT series are available.



## TECHNICAL DATA

Item no.	240004
Number of different light outlets	1
IP Code	IP 65
Assembly	Surface
Assembly details	Ceiling,Wall
Primary nominal voltage	220-240V ~50/60Hz
Safety class	II
Wattage	5 W
Lumen	135 lm
Colour temperature	6000 Kelvin
Beam angle	110 °
Color	white
CRI	70
LXXBXX data	L70B50
Service life	25000 h
Light distribution	symmetric
Light outlet	direct
Width	37.5 cm
Height	17.6 cm
Depth	7.3 cm
Net weight	1.293 kg
Gross weight	1.438 kg

## Accessories

240010	PICTOGRAM FOILS , for P-LIGHT emergency exit light, set of 2, L/H 35.3/16.5 cm
240022	RECHARGEABLE BATTERY , for P-LIGHT, 3.6V, 1000mA, set consists of 2 pieces
240009	PICTOGRAM FOILS , for P-LIGHT emergency exit light, set of 3, L/H 35.3/16.5 cm