




P-LIGHT

recessed fitting, LED, 6000K, round, white, 5W

P-LIGHT suitable for use as emergency lighting for wall and ceiling installation. The two rigid lamp heads are each fitted with a 2W LED. The safety lights are fitted with two built-in Ni-MH rechargeable batteries and an auto test function. The emergency operating time of the luminaires is three hours. The luminaires can be operated permanently switched on / stand-by operation. The electrical connection is directly to the 230V supply. Other variants of the P-LIGHT series are available.



TECHNICAL DATA

Item no.	240006
Number of different light outlets	1
IP Code	IP 20
Assembly	Recessed
Assembly details	Ceiling
Primary nominal voltage	220-240V ~50Hz
Safety class	II
Wattage	5 W
Lumen	120 lm
Colour temperature	6000 Kelvin
Beam angle	90 °
Color	white
CRI	70
LXXBXX data	L70B50
Service life	25000 h
Light distribution	symmetric
Light outlet	direct
Height	6.2 cm
Diameter	12.5 cm
Net weight	0.41 kg
Gross weight	0.477 kg
Shape of cut-out	round

Installation depth	7.5 cm
Installation diameter	9.5 cm

Accessories

240024	RECHARGEABLE BATTERY , for P-LIGHT, 7.2V, 1000mA
--------	--