



FLEXLED ROLL RGB

24V, 41W, 5m, 48 LED/m

Flexible 24V DC LED RGB strip. For simplified mounting the backside is covered with adhesive tape. The power input is given by a 24V direct current power supply unit. We further offer accessory like feed cables and direct connectors. To control the various RGB effects a separately available controller is required.

TECHNICAL DATA

Item no.	552123
IP Code	IP 20
Dimmable	Yes
Dimming technology	Dim-to-Warm
LED distance	2.1 cm
Nominal voltage	24V DC V
Safety class	III
Wattage	41 W
Colour temperature	2000-10000 Kelvin
Beam angle	120 °
Color	copper
Service life	20000 h
Switching cycles	10000
Length	500 cm
Width	1.5 cm
Height	0.2 cm
Net weight	0.078 kg
Gross weight	0.206 kg

Accessories

470651	EASY LIM RF-MINI-RGB-SLAVE , 12V/DC and 24V/DC
550419	DIRECT CONNECTOR , for FLEXLED ROLL RGB 24V up to 15mm wide, max. 50W
470650	EASY LIM RF-MINI-RGB MASTER CONTROLLER , 12V/DC and 24V/DC, with remote controller
1005383	LED power supply , 60W 24V
550418	FEED-IN , for FLEXLED ROLL RGB 24V up to 15mm wide, max. 50W, 50cm