



DELF C 1000 RGB PRO

light bar, 24V, 60 LED

A rigid 24V DC LED RGB profile made from anodized aluminium and plastic. We included a connection lead, a flexible connector and mounting clips. Through the build-in plug-contacts these profiles can be connected directly to each other. The power-input to these profiles, available in several lengths, is made via a separately available 24V direct current power supply. To control the RGB-effects, a controller is required and available as an accessory. This luminaire contains built-in LED lamps.

TECHNICAL DATA

| | |
|--------------------|---------------------|
| Item no. | 631463 |
| IP Code | IP 20 |
| Assembly | Surface |
| Assembly details | Ceiling,Ground,Wall |
| Dimmable | Yes |
| Dimming technology | Dim-to-Warm |
| Wattage | 15 W |
| Colour temperature | 2000-10000 Kelvin |
| Color | aluminium |
| Service life | 20000 h |
| Light outlet | direct |
| Length | 100 cm |
| Width | 2 cm |
| Height | 1.5 cm |
| Net weight | 0.207 kg |
| Gross weight | 0.271 kg |

Accessories

| | |
|--------|---|
| 631472 | MOUNTING CLIPS , for DOLF C PRO light bar, 10 pieces |
| 470581 | POWER LIM 2 RGB MASTER CONTROLLER , 24V, incl. power supply 60W |
| 631474 | FLEXIBLE CONNECTOR , for DOLF C PRO light bar RGB, max. 50W, 12cm |
| 470520 | REMOTE CONTROL , for POWER LIM® 2 master controller, incl. IR recei- ver |
| 470582 | POWER LIM 2 RGB SLAVE CONTROLLER , 24V incl. power supply 60W |
| 631473 | FEED-IN CABLE , for DOLF C PRO light bar RGB, max. 50W, 1.5m |
| 631475 | MOUNTING CLIPS , for DOLF C PRO light bar, 10 pieces, 45° |