



DEL F D

light bar, 12 LED, 3000K, L/W 20.5/1.5 cm, 24V

SLV DEL F D filigree, modular plug & play light bar system made of anodised aluminium and plastic. Feed-in cables, flexible connectors and mounting clips are available as accessories. Thanks to the built-in plug contacts, the profiles can be connected directly to each other. The electrical connection of the profiles, which come in several lengths, is done to a separately available 24V DC power supply. This luminaire includes built-in LED lamps.

TECHNICAL DATA

Item no.	631502
IP Code	IP 20
Assembly	Surface
Assembly details	Ceiling,Ground,Wall
Primary nominal voltage	24V
Safety class	III
Minimum ambient temperature	-20 °C
Maximum ambient temperature	40 °C
Lumen	190 lm
Colour temperature	3000 Kelvin
Beam angle	110 °
Color	aluminium
CRI	80
LXXBXX data	L70B50
Service life	30000 h
Light distribution	symmetric
Light outlet	direct
Length	20.5 cm
Width	1.5 cm
Height	1.4 cm
Net weight	0.043 kg
Gross weight	0.057 kg

Accessories

470502	LED POWER SUPPLY , 12W, 24V
470547	TCI LED POWER SUPPLY , 20W, 24V, incl. strain relief