



DELFD

light bars, 60 LED, RGB, L/W 100.5/1.5 cm, 24V

SLV DELFD RGB filigree, modular plug & play light bar system made of anodised aluminium and plastic. Feed-in cables, flexible connectors and mounting clips are available as accessories. Thanks to the built-in plug contacts, the profiles can be connected directly to each other. The electrical connection of the profiles, which come in several lengths, is done to a separately available 24V DC power supply. A separate controller is needed to control the RGB effects. This luminaire includes built-in LED lamps.

TECHNICAL DATA

Item no.	631540
IP Code	IP 20
Primary nominal voltage	24V
Safety class	III
Minimum ambient temperature	-20 °C
Maximum ambient temperature	40 °C
Beam angle	110 °
Color	aluminium
CRI	80
LXXBXX data	L70B50
Service life	30000 h
Light outlet	direct
Length	100.5 cm
Width	1.5 cm
Height	1.4 cm
Net weight	0.155 kg
Gross weight	0.194 kg

Accessories

470502	LED POWER SUPPLY , 12W, 24V
470547	TCI LED POWER SUPPLY , 20W, 24V, incl. strain relief
631551	CONNECTOR , for DELF D light bars RGB, single colour, 12 cm, max.50W
631550	FEED-IN , for DELF D light bars RGB, single co- lour, 1.5 m, max. 50W