




KALU

wall and ceiling light, double-headed, LED, 3000 K, white/black, 60°

As one would expect, the LED extension of the popular KALU series guarantees the utterly free adjustment of lamp heads. Fitted with dimmable, high output LEDs, the KALU series has just become even more efficient and versatile! Available in matt black or black and white, KALU wall and ceiling light is supplied ready for direct connection to 230V mains supply.



TECHNICAL DATA

Item no.	1000130
Number of different light outlets	2
Rotating or tilting	rotary bar and tiltable
IP Code	IP20
Assembly	Surface
Assembly details	Ceiling, Wall
Dimmable	Yes
Dimming technology	trailing edge
Primary nominal voltage	220-240V ~50/60Hz
Secondary power / voltage	700 mA
Safety class	I
Wattage	31 W
Rated standby power	0.5 W
Stroboscopic effect (SVM)	0.03
Lumen	2000 lm
Colour temperature	3000 Kelvin
Beam angle	60 °
Color	white
CRI	80
LXXBXX data	L70B50
Service life	40000 h
Light distribution	rotational symmetric

Light Source

916610		
		Light outlet
		direct
		Risk Group
		1
		Length
		28 cm
		Width
		8.9 cm
		Height
		16 cm
		Net weight
		1.469 kg
		Gross weight
		1.81 kg
		BIG WHITE Page
		451