




APONI 120

outdoor floor stand, LED, anthracite, 3000 K, IP65

With the aluminium APONI 120 floor stand, the opalescent PC illumination surface is closed off with an aluminium cap. With protection class IP55, it is suitable for outdoor use. A connection box is optionally available for simplified installation. The luminaire, which comes in two sizes, is connected directly to the 230V mains power supply because of the dimmable LED constant current driver. The APONI series also includes wall lights and can therefore be used universally.



TECHNICAL DATA

Item no.	1000683
IP Code	IP65
Dimmable	Yes
Dimming technology	trailing edge
Primary nominal voltage	220-240V ~50/60 Hz
Secondary power / voltage	500 mA
Safety class	I
Wattage	6.3 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	40 °C
Level of inrush current	10 A
Duration of inrush current	40 µs
Lumen	520 lm
Colour temperature	3000 Kelvin
Color	anthracite
CRI	80
Service life	30000 h
Height	120 cm
Diameter	7.2 cm
Net weight	1.944 kg
Gross weight	2.707 kg
BIG WHITE Page	778

Light Source

916573	
--------	---

Accessories

228730	CONNECTION BOX , 3-pin, IP68
--------	---------------------------------