




## Q-LINE CL

**LED Indoor surface-mounted ceiling light, 1m, BAP, black, 4000K**

The Q-LINE ceiling light is optionally available with a white, black, or silver-grey luminaire housing. It is also available with a pure white or warm white LED, and different dimensions. Its high luminance and UGR value of less than 10 make the Q-Line luminaire suitable for workstations. Thanks to the TRIAC dimmable LED driver, the luminaire can be directly connected to the 230 Volt mains voltage supply.



## TECHNICAL DATA

|                                   |                   |
|-----------------------------------|-------------------|
| Item no.                          | 1000689           |
| Number of different light outlets | 1                 |
| IP Code                           | IP 20             |
| Assembly                          | Surface           |
| Assembly details                  | Ceiling           |
| Dimmable                          | Yes               |
| Dimming technology                | trailing edge     |
| Primary nominal voltage           | 220-240V ~50/60Hz |
| Secondary power / voltage         | 900 mA            |
| Safety class                      | I                 |
| Wattage                           | 46 W              |
| Level of inrush current           | 30 A              |
| Duration of inrush current        | 40 µs             |
| Stroboscopic effect (SVM)         | 0.16              |
| Lumen                             | 2300 lm           |
| Colour temperature                | 4000 Kelvin       |
| Beam angle                        | 30 °              |
| Color                             | black             |
| CRI                               | 90                |
| UGR ≤                             | 10                |
| LXXBXX data                       | L70B50            |
| Service life                      | 25000 h           |

## Light Source

|        |                                                 |                                                                   |
|--------|-------------------------------------------------|-------------------------------------------------------------------|
| 916460 | <div><div>A<br/>T<br/>G</div><div>F</div></div> |                                                                   |
|        |                                                 | <div><div>Light distribution</div><div>axis symmetric</div></div> |
|        |                                                 | <div><div>Light outlet</div><div>direct</div></div>               |
|        |                                                 | <div><div>Length</div><div>100 cm</div></div>                     |
|        |                                                 | <div><div>Width</div><div>6 cm</div></div>                        |
|        |                                                 | <div><div>Height</div><div>6 cm</div></div>                       |
|        |                                                 | <div><div>Net weight</div><div>2.261 kg</div></div>               |
|        |                                                 | <div><div>Gross weight</div><div>2.702 kg</div></div>             |
|        |                                                 | <div><div>BIG WHITE Page</div><div>253</div></div>                |