





MEDO 60

ceiling light, LED, 3000K, square, white, 1-10V

The MEDO 60 CL Square has a clear edge, and adds a square version to the MEDO series. Thanks to having an integrated premium LED, it provides bright and uniform illumination. The ceiling light can be converted into a pendant using a suspension kit, and is therefore also ideal for rooms with high ceilings. The built-in LED driver allows direct connection to a mains supply of 120V – 240V.



TECHNICAL DATA

Item no.	1000726
IP Code	IP 20
Assembly	Surface
Assembly details	Ceiling
Primary nominal voltage	220-240V ~50/60Hz
Secondary power / voltage	1000 mA
Safety class	I
Wattage	39 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	40 °C
Rated standby power	0.5 W
Level of inrush current	6 A
Duration of inrush current	30 µs
Stroboscopic effect (SVM)	0.07
Lumen	3800 lm
Colour temperature	3000 Kelvin
Beam angle	105 °
Color	white
CRI	80
UGR ≤	22
LXXBXX data	L70B50
Service life	25000 h

Light Source

916584	
--------	---

Accessories

1001952	MEDO 5m suspension , black
1001950	MEDO 5m suspension , white
135250	SUSPENSION SET , for MEDO round pendant, round, black, 5-wire
470505	EP1 DIMMER , 1-10V, max. 10W
1001951	MEDO 5m suspension , silver-grey
135251	SUSPENSION SET , for MEDO round pendant, round, white, 5-wire
135254	SUSPENSION SET , for MEDO round pendant, round, silver-grey, 5-wire

Risk Group	1
Length	60 cm
Width	60 cm
Height	12.5 cm
Net weight	6.404 kg
Gross weight	8.134 kg
BIG WHITE Page	165