




HELIA

outdoor spot, LED, 3000 K, 35°, anthracite, IP66

The HELIA LED pathway luminaire is equipped with an 8 W high-voltage LED and emits a warm-white light colour. The luminaire is made of aluminium and is connected using the 3 m supply cable with open cable ends directly to the 230V mains supply. Thanks to its IP66 protection class, the luminaire is suitable for outdoor use.



TECHNICAL DATA

Item no.	1000735
Number of different light outlets	1
Rotating or tilting	rotary bar and tiltable
IP Code	IP66
Impact resistance class	IK 04
Impact resistance	0.5 Joule
Primary nominal voltage	220-240V ~50/60 Hz
Secondary power / voltage	500 mA
Safety class	I
Wattage	6.5 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	40 °C
Level of inrush current	4.5 A
Duration of inrush current	30 µs
Lumen	440 lm
Colour temperature	3000 Kelvin
Beam angle	35 °
Color	anthracite
CRI	80
Service life	30000 h
Length	11.5 cm
Height	9.5 cm

Light Source

916573	
--------	---

Accessories

1000736	EARTH SPIKE , for HE-LIA LED SPOT, stainless steel
---------	--

Diameter	5.5 cm
Net weight	0.723 kg
Gross weight	0.976 kg
BIG WHITE Page	817