




## PANEL 60 round

**LED Indoor surface-mounted ceiling light, silver-grey, 3000K**

The LED PANEL 60 comes with several different light and housing colours, and provides a modern and space-saving solution for an efficient type of basic lighting. The high degree of luminous flux provides a pleasant, homogeneous and glare-free lighting feeling. The electrical connection is made directly to the 230V mains voltage supply. This luminaire contains built-in LED lamps.



## TECHNICAL DATA

|                            |                   |
|----------------------------|-------------------|
| Item no.                   | 1000785           |
| IP Code                    | IP 20             |
| Assembly                   | Surface           |
| Assembly details           | Ceiling           |
| Dimmable                   | Yes               |
| Dimming technology         | trailing edge     |
| Number of through-wires    | 40                |
| Primary nominal voltage    | 220-240V ~50/60Hz |
| Secondary power / voltage  | 1000 mA           |
| Safety class               | I                 |
| Wattage                    | 42 W              |
| Level of inrush current    | 9 A               |
| Duration of inrush current | 50 µs             |
| Stroboscopic effect (SVM)  | 0.04              |
| Lumen                      | 3150 lm           |
| Colour temperature         | 3000 Kelvin       |
| Beam angle                 | 110 °             |
| Color                      | grey              |
| CRI                        | 80                |
| UGR ≤                      | 22                |
| LXXBXX data                | L70B50            |
| Service life               | 30000 h           |

## Light Source

|        |                                                                                   |                           |
|--------|-----------------------------------------------------------------------------------|---------------------------|
| 916602 |  |                           |
|        |                                                                                   | <b>Light distribution</b> |
|        |                                                                                   | rotational symmetric      |
|        |                                                                                   | <b>Light outlet</b>       |
|        |                                                                                   | direct                    |
|        |                                                                                   | <b>Height</b>             |
|        |                                                                                   | 5.5 cm                    |
|        |                                                                                   | <b>Diameter</b>           |
|        |                                                                                   | 60 cm                     |
|        |                                                                                   | <b>Net weight</b>         |
|        |                                                                                   | 4.552 kg                  |
|        |                                                                                   | <b>Gross weight</b>       |
|        |                                                                                   | 5.786 kg                  |
|        |                                                                                   | <b>BIG WHITE Page</b>     |
|        |                                                                                   | 274                       |