




## DOLIX OUT QPAR51

square, matt chrome

The DOLIX low-voltage recessed ceiling ring is made from aluminium and is equipped with a glass for protection against splashing water. Rated IP65 it can be used outdoors or in damp areas. To operate the recessed fitting, a matching transformer for low-voltage halogen lamps is required.



## TECHNICAL DATA

|                         |                   |
|-------------------------|-------------------|
| Item no.                | 1001172           |
| Socket                  | GU10              |
| Number of sockets       | 1                 |
| IP Code                 | IP 65             |
| Impact resistance class | IK 02             |
| Impact resistance       | 0.2 Joule         |
| Assembly                | Recessed          |
| Assembly details        | Ceiling           |
| Primary nominal voltage | 220-240V ~50/60Hz |
| Safety class            | II                |
| Wattage                 | 50 W              |
| Color                   | silver            |
| Light outlet            | direct            |
| Length                  | 8.8 cm            |
| Width                   | 8.8 cm            |
| Height                  | 11 cm             |
| Net weight              | 0.197 kg          |
| Gross weight            | 0.23 kg           |
| Shape of cut-out        | round             |
| Installation depth      | 11 cm             |
| Installation diameter   | 6.8 cm            |
| BIG WHITE Page          | 235               |

## Recommended lamp

|         |                                                  |
|---------|--------------------------------------------------|
| 1005273 | QPAR51 GU10 , LED light, 6W 2200 2700K CRI90 36° |
| 1005079 | LED lightbulb QPAR51 , GU10, 3000K, white        |
| 1005076 | LED lightbulb QPAR51 , GU10, 2700K, white        |
| 1005082 | LED lightbulb QPAR51 , GU10, 4000K, white        |