




TRILEDO Double

LED Indoor surface-mounted ceiling light, white, 3000 K, 16 W

The rotating and swivelling ceiling light TRILEDO DOUBLE SQUARE CL is made of aluminium and comes in housing colours of white and black. Thanks to its aluminium lamp head, the cone of light can be individually aligned. Equipped with two LED light sources and an LED driver, the luminaire is ready for direct connection to a 230V mains voltage supply.



TECHNICAL DATA

Item no.	1002008
IP Code	IP20
Assembly	Surface
Assembly details	Ceiling
Primary nominal voltage	220-240V ~50/60 Hz
Secondary power / voltage	350 mA
Safety class	I
Wattage	14 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	30 °C
Number of luminaires at LS B16A	88
Number of luminaires at LS C16A	149
Level of inrush current	2 A
Duration of inrush current	80 µs
Lumen	1280 lm
Colour temperature	3000 Kelvin
Beam angle	38 °
Color	white
CRI	90
Service life	50000 h
Risk Group	1
Length	16.25 cm

Light Source

869620		Width	8.5 cm
		Height	9.5 cm
		Net weight	0.706 kg
		Gross weight	0.855 kg
		BIG WHITE Page	181