





PATTA-I

**LED outdoor recessed ceiling light, angular DL IP65
white 1800-3000 K**

The innovative PATTA-I recessed light is suitable for ceiling thicknesses up to 20 mm. Thanks to its IP65 rating, it is suitable for use outdoors and in wet rooms. The light is available in black, white or silver grey, and in a round or square shape. It is fitted with a powerful, dim-to-warm LED, which allows the light colour to be individually adjusted. Thanks to the integrated LED driver, the light can be connected directly to the 230 V mains voltage.



TECHNICAL DATA

Item no.	1002102
IP Code	IP20/IP65
Impact resistance class	IK 02
Impact resistance	0.2 Joule
Dimmable	Yes
Dimming technology	Dim-to-Warm, Leading edge, trailing edge
Primary nominal voltage	220-240V ~50/60 Hz
Secondary power / voltage	350 mA
Safety class	II
Wattage	7.3 W
Level of inrush current	2 A
Duration of inrush current	40 µs
Lumen	44-440 lm
Colour temperature	1800-3000 Kelvin
Beam angle	38 °
Color	white
CRI	95
Service life	30000 h
Length	8 cm
Width	8 cm
Height	4 cm
Net weight	0.247 kg

Light Source

916436		Gross weight	0.293 kg
		Shape of cut-out	round
		Installation depth	6 cm
		Installation diameter	6 cm
		BIG WHITE Page	162