






DOWNUNDER OUT

round WL Outdoor LED recessed wall light, anthracite, 3000 $\ensuremath{\mathrm{K}}$

A wall-mounted light such as the DOWNUNDER OUT is protected against water jets from all directions and also against dust deposits. Protection category IP55 guarantees problem-free use outdoors. Here at SLV, we work hard on our service and our lights, to ensure that you are satisfied. This attitude and our commitment to quality and design have allowed us to enjoy success for a lmost 40 years. For this reason, we offer a 5-year warranty for our products.



TECHNICAL DATA

Item no.	1002868
IP Code	IP65
Impact resistance class	IK 02
Primary nominal voltage	100-240V ~50/60 Hz
Secondary power / voltage	500 mA
Safety class	I
Wattage	4.3 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	40 °C
Level of inrush current	15 A
Duration of inrush current	300 µs
Lumen	150/160 lm
Colour temperature	3000/4000 Kelvin
Color	anthracite
CRI	80
Service life	30000 h
Risk Group	1
Depth	4.4 cm
Diameter	14 cm
Net weight	0.43 kg
Gross weight	0.511 kg
BIG WHITE Page	911



Light Source

916443	A E
--------	-----