




FLATT SENSOR

Outdoor LED surface-mounted wall light, 3000 K, IP54, anthracite

Would you like a wall light which can be fitted effortlessly? This should have a safety class of at least IP 65, and therefore be thus dustproof and protected from water spray from various directions. Our FLATT WL has IP 65 and is suitable for providing a surface, path or terrace with fantastic illumination. Thanks to the built-in motion sensor, the luminaire makes a decisive contribution to providing safe lighting. Are you looking for amazing light for your outdoor area? This is provided by the built-in Premium LED of the FLATT POLE 65 floor stand. Incidentally, the FLATT POLE 65 gives you even more advantages as a part of the SLV family. Because we have been successful with our lighting concepts for 40 years, and keep setting the bar higher for ourselves and our products.




TECHNICAL DATA

Item no.	1002954
IP Code	IP54
Impact resistance class	IK 03
Impact resistance	0.35 Joule
Primary nominal voltage	100-240V ~50/60 Hz
Secondary power / voltage	300 mA
Safety class	I
Wattage	13 W
Ambient temperature	40 °C
Minimum ambient temperature	-25 °C
Maximum ambient temperature	40 °C
Level of inrush current	5 A
Duration of inrush current	100 µs
2	100 μ3
Lumen	500/530 lm
Lumen	500/530 lm
Lumen Colour temperature	500/530 lm 3000/4000 Kelvin
Lumen Colour temperature Color	500/530 lm 3000/4000 Kelvin anthracite/anthracite
Lumen Colour temperature Color CRI	500/530 Im 3000/4000 Kelvin anthracite/anthracite
Lumen Colour temperature Color CRI Service life	500/530 lm 3000/4000 Kelvin anthracite/anthracite 80 30000 h
Lumen Colour temperature Color CRI Service life Risk Group	500/530 lm 3000/4000 Kelvin anthracite/anthracite 80 30000 h
Lumen Colour temperature Color CRI Service life Risk Group Width	500/530 lm 3000/4000 Kelvin anthracite/anthracite 80 30000 h 1 18 cm



Light Source



Net weight	2.008 kg
Gross weight	2.248 kg
BIG WHITE Page	898