




NOTAPO I

Indoor recessed wall light 3000 K white

Aluminium recessed wall light NOTAPO I WL. The invisibly installed LED emits its light indirectly onto the surface to be illuminated. This makes glare-free illumination of walkways and staircases possible, for example. The NOTAPO I recessed fitting is available with a white housing. An installation frame and a mounting box for installation in masonry are optionally available. This luminaire contains built-in LED lamps.



TECHNICAL DATA

Item no.	1002979
IP Code	IP20
Secondary power / voltage	700 mA
Safety class	III
Wattage	2.2 W
Maximum ambient temperature	40 °C
Lumen	6 lm
Colour temperature	3000 Kelvin
Color	white
CRI	90
Service life	35000 h
Width	3.6 cm
Height	10.5 cm
Depth	3.8 cm
Net weight	0.086 kg
Gross weight	0.126 kg
Shape of cut-out	square
Installation length	10 cm
Installation width	2.8 cm
Installation depth	5 cm
BIG WHITE Page	159

Light Source

954799	
--------	---

Accessories

1007213	LED DRIVER , 10 W, 700 mA, PHASE, incl. strain relief
1007216	LED driver 3 W , 700 mA incl. strain relief
1007229	LED driver 25 W 150-700 mA DALI TOUCH
1002981	NOTAPO I and II WL , installation frame