




## GALEN 60 SP

outdoor single colour LED profile anthracite CCT switch 3000/4000 K

Thanks to the integrated mounting bracket and the splash-proof connection cables, the GALEN LED profile can be installed quickly and easily on walls, floors, or ceilings. It is most suitable as a form of lighting for displays and signs. Added to this is the practical CCT switch, which provides added flexibility as it allows the light colour to be adjusted between 3000 K (warm white) and 4000 K (neutral white) using an external switch. Robustly made and featuring high-performance LEDs, GALEN is perfect for creating effective or functional lighting in the outdoor areas of shops, hotels, restaurants, or in commercial buildings.



## TECHNICAL DATA

Item no.	1003447
IP Code	IP65
Impact resistance class	IK 03
Impact resistance	0.35 Joule
Number of through-wires	12
Primary nominal voltage	220-240V ~50/60 Hz
Secondary power / voltage	450 mA
Safety class	I
Wattage	18 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	45 °C
Number of luminaires at LS B16A	12
Level of inrush current	20 A
Duration of inrush current	350 µs
Lumen	1570/1570 lm
Colour temperature	3000/4000 Kelvin
Color	anthracite
CRI	80
Service life	54000 h
Risk Group	1
Width	60 cm
Height	6.2 cm

## Light Source

916615	
--------	---

## Accessories

231961	CONNECTION CABLE , for GALEN outdoor wall light, black, 1 m
231960	CONNECTION CABLE , for GALEN outdoor wall light, black, 5 m

Depth	11.3 cm
Net weight	1.684 kg
Gross weight	1.832 kg
BIG WHITE Page	808