




## GALEN 120

**SP LED PROFILE Outdoor Single Colour CCT switch 3000/4000 K**

Thanks to the integrated mounting bracket and the splash-proof connection cables, the GALEN LED profile can be installed quickly and easily on walls, floors, or ceilings. It is most suitable as a form of lighting for displays and signs. Added to this is the practical CCT switch, which provides added flexibility as it allows the light colour to be adjusted between 3000 K (warm white) and 4000 K (neutral white) using an external switch. Robustly made and featuring high-performance LEDs, GALEN is perfect for creating effective or functional lighting in the outdoor areas of shops, hotels, restaurants, or in commercial buildings.



## TECHNICAL DATA

Item no.	1003448
IP Code	IP65
Impact resistance class	IK 03
Impact resistance	0.35 Joule
Number of through-wires	10
Primary nominal voltage	220-240V ~50/60 Hz
Secondary power / voltage	900 mA
Safety class	I
Wattage	34 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	45 °C
Number of luminaires at LS B16A	10
Level of inrush current	25 A
Duration of inrush current	500 µs
Lumen	3000/3100 lm
Colour temperature	3000/4000 Kelvin
Color	anthracite
CRI	80
Service life	54000 h
Risk Group	1
Width	120 cm
Height	6.2 cm

## Light Source

916553	
--------	---

## Accessories

231961	CONNECTION CABLE , for GALEN outdoor wall light, black, 1 m
231960	CONNECTION CABLE , for GALEN outdoor wall light, black, 5 m

Depth	11.3 cm
Net weight	2.779 kg
Gross weight	3.021 kg
BIG WHITE Page	808