




L-LINE OUT 60 FL

Outdoor LED free-standing light anthracite CCT switch 3000/4000 K

Whether in gardens, along the paths and driveways of residential buildings, hotels or restaurants-with its variety of lights, the L-LINE OUT family lights the way outdoors. Despite their individual differences, the individual members share a design vocabulary in L-shape, which stands out with its clear lines. And when it comes to lighting technology, there are no compromises: the choice of light colour (3000/4000 K), which can be selected during the easy installation process, and IP protection class 65 are just some of the benefits of the L-LINE OUT.



TECHNICAL DATA

Item no.	1003535
Number of different light outlets	1
IP Code	IP65
Impact resistance class	IK 02
Impact resistance	0.2 Joule
Primary nominal voltage	220-240V ~50/60 Hz
Secondary power / voltage	500 mA
Safety class	I
Wattage	11.5 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	45 °C
Level of inrush current	10 A
Duration of inrush current	40 µs
Lumen	780/800 lm
Colour temperature	3000/4000 Kelvin
Color	anthracite
CRI	80
Service life	30000 h
Risk Group	0
Length	50 cm
Width	10 cm
Height	10 cm

Light Source

916337	
--------	---

Accessories

228730	CONNECTION BOX , 3-pin, IP68
--------	---------------------------------

Net weight	1.706 kg
Gross weight	2.147 kg
BIG WHITE Page	763