




L-LINE OUT WL

Outdoor LED wall-mounted light anthracite CCT switch 3000/4000 K


With its linear light variety, the L-LINE OUT family lights the way outdoors. Despite their individual differences, the individual members speak a common language of form, encapsulated in the clean lines of the letter "L". As far as lighting technology is concerned, there are no compromises: the CCT switch for easy selection of light colour temperature (3000 or 4000 K) prior to installation), the straightforward installation process, and a protection rating of IP 65 are just some of the features that make the L-LINE OUT surface-mounted wall light a winner.



TECHNICAL DATA

| | |
|-----------------------------------|--------------------|
| Item no. | 1003539 |
| Number of different light outlets | 1 |
| IP Code | IP65 |
| Impact resistance class | IK 02 |
| Impact resistance | 0.2 Joule |
| Number of through-wires | 10 |
| Primary nominal voltage | 220-240V ~50/60 Hz |
| Secondary power / voltage | 350 mA |
| Safety class | I |
| Wattage | 7 W |
| Minimum ambient temperature | -20 °C |
| Maximum ambient temperature | 45 °C |
| Level of inrush current | 10 A |
| Duration of inrush current | 40 µs |
| Lumen | 500/570 lm |
| Colour temperature | 3000/4000 Kelvin |
| Color | anthracite |
| CRI | 80 |
| Service life | 30000 h |
| Risk Group | 0 |
| Width | 15 cm |
| Height | 10 cm |

Light Source

| | | | |
|--------|---|-----------------------|----------|
| 916406 |  | Depth | 10 cm |
| | | Net weight | 1.024 kg |
| | | Gross weight | 1.237 kg |
| | | BIG WHITE Page | 921 |