



## NUMINOS® MOVE DL XL

Indoor LED recessed ceiling light black/white 3000K  
40° rotating and pivoting

Design, technology and function in perfection: NUMINOS is the light system from SLV that combines everything. With a variety of downlights and spotlights, you provide a thousand lighting design options. Also with the NUMINOS® MOVE DL XL recessed ceiling light, which convinces with the best workmanship and lighting quality. Ideal for unobtrusive, modern and space-saving lighting that draws the focus to objects or the room. The recessed ceiling light convinces with a power consumption of 37.4 watts, luminous flux of 3550 lumens, colour temperature of 3000 Kelvin and a colour reproduction index of 90. This means that easy installation is a mere formality. When to choose NUMINOS from SLV – modular diversity awaits you.

## TECHNICAL DATA

|                                   |                         |
|-----------------------------------|-------------------------|
| Item no.                          | 1003725                 |
| Number of different light outlets | 1                       |
| Rotating or tilting               | rotary Bar and tiltable |
| IP Code                           | IP 20                   |
| Impact resistance class           | IK 02                   |
| Impact resistance                 | 0.2 Joule               |
| Assembly                          | Recessed                |
| Assembly details                  | Ceiling                 |
| Secondary power / voltage         | 1050 mA                 |
| Safety class                      | III                     |
| Wattage                           | 37.4 W                  |
| Minimum ambient temperature       | -20 °C                  |
| Maximum ambient temperature       | 40 °C                   |
| Lumen                             | 3550 lm                 |
| Colour temperature                | 3000 Kelvin             |
| Beam angle                        | 40 °                    |
| Color                             | black                   |
| CRI                               | 90                      |
| UGR ≤                             | 19                      |
| LXXBXX data                       | L80B50                  |
| Service life                      | 50000 h                 |
| Light distribution                | rotational symmetric    |

## Light Source

|        |                                                                                   |
|--------|-----------------------------------------------------------------------------------|
| 791823 |  |
|--------|-----------------------------------------------------------------------------------|

## Accessories

|         |                                                                                             |
|---------|---------------------------------------------------------------------------------------------|
| 1006152 | Numinos® XL Reducing ring , round 240/180mm white                                           |
| 1006151 | Numinos® XL Reducing ring , round 240/180mm black                                           |
| 1004800 | NUMINOS® XL , diffuser Frosted                                                              |
| 1004071 | LED driver 4.2-50W 1050mA DALI                                                              |
| 1006454 | RF module Casambi for LED bridge driver , single colour                                     |
| 1006154 | Numinos® XL Reducing ring , square 240/180mm white                                          |
| 1006199 | RF module Zigbee for DALI LED bridge driver , single colour                                 |
| 1004798 | NUMINOS® XL , diffuser Ellipse                                                              |
| 1006153 | Numinos® XL Reducing ring , square 240/180mm black                                          |
| 1004059 | LED driverm 40W multi mA                                                                    |
| 1006461 | LED bridge driver , 42W, 1050mA for NUMINOS®, including radio interface for RF module, DALI |
| 1004066 | LED driver , 28-40W 1000mA PHASE                                                            |
| 1004801 | NUMINOS® XL , diffuser Wabe                                                                 |
| 1004799 | NUMINOS® XL , diffuser Prisma                                                               |

|                       |         |
|-----------------------|---------|
| Light outlet          | direct  |
| Risk Group            | 1       |
| Height                | 11.8 cm |
| Diameter              | 19 cm   |
| Net weight            | 0.7 kg  |
| Gross weight          | 0.89 kg |
| Shape of cut-out      | round   |
| Installation depth    | 13 cm   |
| Installation diameter | 17.5 cm |
| BIG WHITE Page        | 87      |