



NUMINOS® DL S

Indoor LED recessed ceiling light black/black 3000K
55° gimballed, rotating and pivoting, including leaf
springs

The NUMINOS light system from SLV combines technology, design and functionality like no other. With a variety of downlights and spotlights, you provide a thousand lighting design options. Like with the NUMINOS® DL S recessed ceiling light, which impresses with its high-quality workmanship and light. In this way, you can create unobtrusive, modern and space-saving lighting that draws the focus to objects or the room. The recessed ceiling light can convince with a power consumption of 8.6 watts, luminous flux of 690 lumens, colour temperature of 3000 Kelvin and a high colour reproduction index of over 90. Installation is then done in no time at all. When do you choose NUMINOS® from SLV?

TECHNICAL DATA

| | |
|-----------------------------------|----------------------|
| Item no. | 1003799 |
| Number of different light outlets | 1 |
| IP Code | IP 20 / IP 44 |
| Impact resistance class | IK 02 |
| Impact resistance | 0.2 Joule |
| Assembly | Recessed |
| Assembly details | Ceiling |
| Secondary power / voltage | 250 mA |
| Safety class | III |
| Wattage | 8.6 W |
| Minimum ambient temperature | -20 °C |
| Maximum ambient temperature | 40 °C |
| Lumen | 690 lm |
| Colour temperature | 3000 Kelvin |
| Beam angle | 55 ° |
| Color | black |
| CRI | 90 |
| UGR ≤ | 22 |
| LXXBXX data | L80B50 |
| Service life | 50000 h |
| Light distribution | rotational symmetric |
| Light outlet | direct |

Light Source

| | |
|--------|---|
| 791815 |  |
|--------|---|

Accessories

| | |
|---------|--|
| 1006136 | Numinos® XS Reducing ring , round 160/70mm white |
| 1006458 | LED bridge driver , 12W, 250mA for NUMINOS®, including radio interface for RF module, DALI |
| 1006135 | Numinos® XS Reducing ring , round 160/70mm black |
| 1004789 | NUMINOS® S , diffuser Wabe |
| 1004067 | LED driver , 15W 250mA DALI |
| 1004788 | NUMINOS® S , diffuser Frosted |
| 1004787 | NUMINOS® S , diffuser Prisma |
| 1004786 | NUMINOS® S , diffuser Ellipse |
| 1006454 | RF module Casambi for LED bridge driver , single colour |
| 1004058 | LED driver , 6.5-10W 250mA |
| 1006199 | RF module Zigbee for DALI LED bridge driver , single colour |
| 1006137 | Numinos® XS Reducing ring , square 160/70mm black |
| 1006138 | Numinos® XS Reducing ring , square 160/70mm white |
| 1004055 | LED driver , 6.5-10W 250mA PHASE |

| | |
|-----------------------|----------|
| Risk Group | 1 |
| Height | 5.2 cm |
| Diameter | 8 cm |
| Net weight | 0.163 kg |
| Gross weight | 0.193 kg |
| Shape of cut-out | round |
| Installation depth | 5.5 cm |
| Installation diameter | 6.8 cm |
| BIG WHITE Page | 87 |